


NORTH



Our Services
 Architecture Design
 Structure Design
 Interior Design
 Estimating & Costing
 Building Construction With Material

Outer Wall- 10"
 Inner Wall- 05"

EAST

SCHEDULE OF DOOR & WINDOWS			
SP. L	B	H	SILL H.
MD 4'0"		07'00"	00'00"
D 3'6"		07'00"	00'00"
D1 3'0"		07'00"	00'00"
D2 2'6"		07'00"	00'00"
W1 4'0"		04'00"	03'00"
W2 3'0"		04'00"	03'00"
V 2'0"		01'06"	08'06"

Details Of Stair:-

Ceiling Height :- 10'
 Height Of Stair:- 5'
 Height Of Riser:- 6"
 Width Of Trade :- 10"
 Width Of Stair :- 3'-6"
 Width Of Landing :- 3'-6"
 Steps Of Stair :- 19

CLIENT :- ASHWANI SIR

PROJECT :- GROUND FLOOR PLAN


SCALE:-	1:100	ISSUED	02.12.25
Plan Number:-	01		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		
Jaypro Infratech Pvt.Ltd.			

NORTH

WEST

EAST

SOUTH



Our Services
 Architecture Design
 Structure Design
 Interior Design
 Estimating & Costing
 Building Construction With Material

Outer Wall- 10"
 Inner Wall- 05"

SCHEDULE OF DOOR & WINDOWS			
SP. L	B	H	SILL H.
MD	4'0"	07'00"	00'00"
D	3'6"	07'00"	00'00"
D1	3'0"	07'00"	00'00"
D2	2'6"	07'00"	00'00"
W1	4'0"	04'00"	03'00"
W2	3'0"	04'00"	03'00"
W3	2'6"	04'00"	03'00"
V	2'0"	01'06"	08'06"

Details Of Stair:-
 Ceiling Height :- 10'
 Height Of Stair:- 5'
 Height Of Riser:- 6"
 Width Of Trade :- 10"
 Width Of Stair :- 3'-6"
 Width Of Landing :- 3'-6"
 Steps Of Stair :- 19

CLIENT :- ASHWANI SIR

PROJECT :FIRST FLOOR PLAN

SCALE:-	1:100	ISSUED	02.12.25
Plan Number:-	01		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		


Jaypro Infratech Pvt.Ltd.

Office Address: 1st Floor, Pandooi Place, Boring Road, Patna- 80001

NORTH

WEST

SOUTH



Our Services

**Architecture Design
Structure Design
Interior Design
Estimating & Costing
Building Construction With Material**

Outer Wall- 10"
Inner Wall- 05"

EAS

SCHEDULE OF DOOR & WINDOWS

SP.	L	B	H	SILL H.
MD	4'0"		07'00"	00'00"
D	3'6"		07'00"	00'00"
D1	3'0"		07'00"	00'00"
D2	2'6"		07'00"	00'00"
W1	4'0"		04'00"	03'00"
W2	3'0"		04'00"	03'00"
W3	2'6"		04'00"	03'00"
V	2'0"		01'06"	08'06"


Details Of Stair:-

Celling Height :- 10'
Height Of Stair:- 5'
Height Of Riser:- 6"
Width Of Trade :- 10"
Width Of Stair :- 3'-6"
Width Of Landing :- 3'-6"
Steps Of Stair :- 19

CLIENT :- ASIWANI SIR

PROJECT : SECOND FLOOR PLAN

SCALE:-	1:100	ISSUED	02.12.25
Plan Number:-	01		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :-

PROJECT :- Column Layout Details

SCALE:- 1:100 ISSUED BY: 25.11.06

Plan Number:- 01 ISSUED 05.11.2018

Design By Er.Rishav Kumar


Checked By Er. Jayprakash Kumar

Approved By Jaypro Infratech Pvt.Ltd.




JAYPRO INERATECH PVT. LTD.

Office Address: 1st Floor, Pandooj

Place, Boring Road, Patna- 80001



█ C1-(10"X18")




PILE DETAILS

Pile	DIA	DEPTH	DIA OF UR	No. OF UR	STEEL	RINGS	No. of Piles
PC1	12"	26ft	30"	2	5-T12 mm	T8 mm @ 7" c/c	48

PILE CAP DETAILS

Pile Cap	Pile Dia	Pile Cap Size	Pile Cap Depth (inch)	(Bottom Layer Mat)		(Top Layer Mat-Inverted)		Pile Group
				Main Steel (b') (Lower Level)	Dist. Steel (t') (Upper Level)	Main Steel (b') (Upper Level)	Dist. Steel (t') (Lower Level)	
PC1	12"	5x2x4"	18"	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	
PC2	12"	4x2x2x2x2x4"	18"	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	
PC3	12"	4x2x2x2x2x4"	18"	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	T12 @ 4" c/c	



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
 COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
 FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
 ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :-
 ASHWANI SIR

PROJECT :- PILE CAP Details

SCALE:-	1:100	ISSUED	12.04.25
Plan Number:-	01		
Design By	Er. Rishav Kumar		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		

TECHNICAL NOTES & INSTRUCTIONS:-

- NOTES AND INSTRUCTIONS INDICATED BELOW SHALL BE FOLLOWED WITH DUE RESPONSIBILITY BY ENGINEER IN-CHARGE DURING EXECUTION OF THE PROJECT.
- THE ENGINEER IN-CHARGE SHALL STUDY IN DEPTH THE ARCHITECTURAL/STRUCTURAL DRAWINGS OF THE BUILDING / STRUCTURE ENCLOSED, BEFORE EXECUTION AND AMBIGUITY IF ANY NOTICED BY HIM SHALL BE REPORTED TO CONSULTANT, FOR NECESSARY ACTION. ALL DIMENSIONS ARE IN MM FOLLOW WRITTEN DIMENSION ONLY.
- ONLY STEEL SHUTTERING / CENTERING SHALL BE USED AT WORK SITE FOR CONSTRUCTION OF R.C.C. FRAMED BUILDING.
- QUALITY AND MIX PROPORTION OF MATERIALS TO BE USED IN CONCRETING I.E. WATER / CEMENT / SAND / CHIPS SHALL BE STRICTLY AS PER DESIGN MIX REPORT.
- THE CRUSHING STRENGTH OF CUBES PREPARED WITH CONC. MIX AT WORK SITE SHALL CONFORM THE ACCEPTANCE CRITERIA AS MENTIONED IN I.S. 456, 2000.
- COVER BLOCK WITH PROPER SIZE & SPECIFIED STRENGTH SHALL BE PROVIDED IN SLAB / BEAM / COLUMN / FOUNDATION BEFORE R.C.C. CASTING @ SPACE NOT EXCEEDING ONE METER C/C.
- COVER BLOCK SHALL BE PROPERLY TIED WITH THE REINFORCEMENT FOR FIXITY DURING CONCRETING.
- IN CASE OF PILE FOUNDATION IT IS ESSENTIAL TO HAVE ACTUAL PILE LOAD TEST REPORT ALONG WITH PILE CAPACITY BASED ON SOIL PARAMETERS. SO IT IS INSTRUCTED TO GET THE ACTUAL PILE LOAD TEST REPORT BEFORE EXECUTION AND REPORT TO CONSULTANT FOR REVIEW, AND FINAL CONCLUSION.
- IN CASE OF PILE FOUNDATION HAVING HIGH WATER TABLE USE BENTONITE SOLUTION, CASING AND QUICK SETTING CEMENT, THE ENGINEER IN-CHARGE SHALL TAKE FINAL DECISION AS PER ACTUAL SITE CONDITION.
- ALL CONCRETE SHALL BE MACHINE MIXED AND PROPERLY COMPAKTED BY VIBRATOR.
- NOMINAL COVER (I.E. CLEAR CONCRETE COVER TO ALL REINFORCEMENTS, INCLUDING LINKS) FOR FOUNDATION = 50, PILE CAP - 75, COLUMN = 40, BEAM = 30 AND SLAB = 25mm HALL BE PROVIDED.
- PROPER CURING OF R.C.C. SLAB / COLUMN / FOUNDATION / B/W PLASTER ETC. SHALL BE PROVIDED.
- PROPER ARRANGEMENT FOR SOAKING OF BRICKS SHALL BE ENSURED BY FIELD ENGRS.
- BEFORE PLACING OF REINFORCEMENT POLYTHENE SHEET SHALL DE SPREAD OVER SHUTTERING TO PREVENT CEMENT SLURRY FROM CONC. MIX.
- BEFORE CASTING REINFORCEMENT PLACED SHALL BE DUELY MEASURED BY ENGR INCHARGE.
- L.D.C = LENGTH OF DEVELOPMENT LENGTH WHICH IS 30 DIA.
- LDC = EFFECTIVE DEVELOP LENGTH CONSIDERING COMPRESSION 39X BAR DIA.
- LAP SPlice, NOT MORE THAN 50% OF AREA OF STEEL (LONG) IN COLUMN SLABS SHALL BE SPACED AT ANY ONE SECTION, LAPPING OR WELDING OF RT. SHALL BE STAGGERED.
- IT SHALL BE WITHIN THE LAPPING ZONE AS SHOWN IN THE DRG. THE LAP LENGTH SHALL NOT BE LESS THAN DEVELOPMENT LENGTH OF ROD AND 30 TIMES DIA OF BAR WHICH IS GREATER.
- LAP SPLICE IN BEAM SPAN LESS THAN 12M SHALL BE AVOIDED IN NORMAL CASE. IN LONGER SPAN (L > 12m) LAP SHALL BE PROVIDED AS PER APPROVED STR. DRG.
- ONLY WRITTEN DIMENSIONS ARE TO BE FOLLOWED.
- GRID LINE SHOWS CL OF WALLS.
- THE FORM WORK FOR (SPAN=4M) BEAMS & SLAB SHALL BE SO ASSEMBLED AS TO PROVIDE CAMBER AS FOLLOWS :-
 - CAMBER FOR NORMAL BEAMS SHALL BE 1 IN 250 OF THE SPAN OR 4MM PER METER OF SPAN AT THE CENTRAL POINT
 - FOR CANTILEVER BEAMS (SLAB CAMBER AT THE FREE END SHALL BE SPAN / 50 OF THE PROJECTED LENGTH)
- BEFORE R.C.C. CASTING OF BEAMS/SLAB FORM WORK SHALL BE CHECKED PROPERLY TO AVOID DEFLECTION.
- REMOVAL OF FORM WORKS SHALL BE AS PER STRIPPING TIME PRESCRIBED VIDE CL. 11.3 OF I.S. 456-2000 WHICH SHALL BE CHECKED BY E.E./A.E.
- IN FRAME STRUCTURE ALL EXTERNALS STAIR WALL SHALL BE 10"THICK AND INTERNAL WALL SHALL BE 5" THICK, EXCEPT MENTIONED.
- NECESSARY ARRANGEMENTS SHALL BE MADE FOR PLINTH PROTECTION OF BUILDING AT LEVEL DECIDED BY E.E. TO AVOID WATER LOGGING AROUND BUILDING THE WIDTH SHALL BE DECIDED AS PER ACTUAL SITE CONDITION BY ENGINEER IN-CHARGE.
- WATER PROOFING COMPOUND SHALL BE USED IN CASTING OF SUNKEN SLAB & TERRACE FLOOR SLAB TO PREVENT SEEPAGE.
- ALL DESIGN MIX CONCRETE OF GRADE M 25 HAVING MINIMUM CEMENT CONTENT 300 kg/m³, Max. W/C = 0.5 FOR COARSE AGGREGATE 20 mm SIZE. CASTING SHOULD BE DONE AS PER MIX DESIGN

NOTES:-2

1. ALL DIMENSIONS ARE IN IN FEET AND INCHES
2. ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.
3. ALL TOR STEEL YIELD STRENGTH 500 N/mm .
4. ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.
5. CLEAR COVER TO MAIN STEEL
40 MM IN PILES, 20mm IN SLAB,
25mm IN BEAM, 40mm IN COLUMN.
6. ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
7. ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
8. WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO COLUMN UP-TO A LENGTH EQUAL TO 50X BAR DIA DISTANCE MEASURED FROM COLUMN FACE
9. BARS TO BE CUT & BENT NEAR OPENINGS/POCKETS.

CLIENT :-

ASHWANI SIR

PROJECT :-

GROUND FLOOR TIE BEAM


SCALE

1:100 ISSUED 01.11.2013

SCALE:-	1:100	ISSUED	04.11.2023
Plan Number:-	01		
Design By	Ar. Soni Kumari	Er. Jayprakash Kumar	
Checked By			
Approved By	Jaypro Infratech Pvt.Ltd.		




JAYPRO INFRATECH PVT. LTD.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001




SLAB. BEAM SECTION

BEAM REINFORCEMENT INDEX								
BEAM MKD	SIZE		REINFORCEMENT				STIRRUPS	
			TOP REINF.		BOT. REINF.			
	B	D	TOP.M (t1)	TOP.EXT (t2)	BOT.M (b1)	BOT.EXT (b2)	S1	S2
SB1	10"	15"	3-T16	2-T12	3-T16	2-T12	T8@5" c/c	T8@5" c/c



Follow Now
Insta Id: [jaypro_infratech](#)
Facebook Page: [jaypro_infratech](#)




E-mail id: info@jayproinfratech.com, www.jayproinfratech.com, Call Now: 9835852462, 7277008312.



SLAB. BEAM SECTION
Rings 8mm@ (5"+8"+5") c/c for all beams

BEAM REINFORCEMENT INDEX

BEAM MKD	SIZE		REINFORCEMENT				STIRRUPS	
			TOP REINF.		BOT. REINF.			
	B	D	TOP.M (t1)	TOP.EXT. (t2)	BOT.M (b1)	BOT.EXT. (b2)	S1	S2
SB1	10"	18"	3-T16	2-T12	3-T16	2-T12	T8@5" c/c	T8@5" c/c



TECHNICAL NOTES & INSTRUCTIONS:-

- NOTES AND INSTRUCTIONS INDICATED BELOW SHALL BE FOLLOWED WITH DUE RESPONSIBILITY BY ENGINEER IN-CHARGE DURING EXECUTION OF THE PROJECT.
- THE ENGINEER IN-CHARGE SHALL STUDY IN DEPTH THE ARCHITECTURAL/STRUCTURAL DRAWINGS AND TAKE APPROPRIATE MEASURES DURING EXECUTION AND AMBIGUITY IF ANY NOTICED BY HIM SHALL BE REPORTED TO CONSULTANT FOR NECESSARY ACTION.
- ONLY STEEL SHUTTERING / CENTERING SHALL BE USED AT WORK SITE FOR CONSTRUCTION OF R.C.C. FRAMED BUILDING.
- QUALITY AND MIX PROPORTION OF MATERIALS TO BE USED IN CONCRETING I.E. WATER / CEMENT / SAND / CHIPS SHALL BE STRICTLY AS PER DESIGN MIX REPORT.
- THE CEMENT CUBIC CONCRETE TEST CUBE PRECASTED ON CONCRETE WORK SITE SHALL CONFORM THE ACCEPTANCE CUBIC TEST CUBE MENTIONED IN I.S. 456-2000.
- COVER BLOCK WITH PROPER SIZE & SPECIFIED STRENGTH SHALL BE PROVIDED IN SLAB / BEAM / COLUMN / FOUNDATION BEFORE R.C.C. CASTING @ SPACE NOT EXCEEDING ONE METER C.C.
- COVER BLOCK SHALL BE PROPERLY TIED WITH THE REINFORCEMENT FOR FIXITY DURING CONCRETE CASTING.
- IN CASE OF PILE FOUNDATION IT IS ESSENTIAL TO HAVE ACTUAL PILE LOAD TEST REPORT ALONG WITH PILE CAPACITY BASED ON SOIL PARAMETERS. SO IT IS INSTRUCTED TO TAKE THE ACTUAL PILE LOAD TEST REPORT BEFORE EXECUTION AND REPORT TO CONSULTANT FOR PILE TEST AND FINAL CONCLUSIONS.
- IN CASE OF PILE FOUNDATION HAVING HIGH WATER TABLE USE BENTONITE SOLUTION, CASING AND QUICK SETTING CEMENT. THE ENGINEER IN-CHARGE SHALL TAKE FINAL DECISION AS PER ACTUAL SITE CONDITION.
- ALL CONCRETE SHALL BE MACHINE MIXED AND PROPERLY COMPAKTED BY VIBRATOR.
- NOMINAL COVER (I.E. CLEAR CONCRETE COVER TO ALL REINFORCMENTS, INCLUDING LINKS) FOR FOUNDATION = 4 PILE CAP - 75, COLUMN = 40, BEAM = 30 AND SLAB = 25mm HALL BE PROVIDED.
- PROPER CURING OF R.C.C. SLAB / COLUMN / FOUNDATION / B/W PLASTER ETC. SHALL BE PROVIDED.
- PROPER ARRANGEMENT FOR SOAKING OF BRICKS SHALL BE ENSURED BY FIELD ENGRS. BEFORE PLACING OF REINFORCEMENT POLYTHENE SHEET SHALL BE SPREAD OVER SHUTTERING TO PREVENT CEMENT SLURRY FROM CONC. MIX.
- BEFORE CASTING REINFORCEMENT PLACED SHALL BE DULY MEASURED BY ENGR INCHARGE.
- L.D.C = EFFECTIVE DEVELOP. LENGTH CONSIDERING TENSION 49X BAR DIA.
- 19(A) AP SPAN = 12M, LENGTH OF REINFORCEMENT = 12M, DIA OF REINFORCEMENT = 12MM. IT SHALL BE SPANNED AT ANY ONE SECTION, LAPPING OR WELDING OF RT. SHALL BE STAGGERED. IT SHALL BE WITHIN THE LAPPING ZONE AS SHOWN IN THE DRG. THE LAP LENGTH SHALL NOT BE LESS THAN DEVELOPMENT LENGTH OF ROD AND 30 TIMES DIA OF BAR WHICH IS GREATER. 19(B) LAP SPLICE IN BEAM SPAN LESS THAN 12M SHALL BE AVOIDED IN NORMAL CASE. IN LONGER SPAN (L > 12M) LAP SHALL BE PROVIDED AS PER APPROVED STR. DRG.
- ONLY WRITTEN DIMENSIONS ARE TO BE FOLLOWED.
- GRID LINES SHOWS CL. OF WALLS.
- THE FORM WORK FOR (SPAN >4M) BEAMS & SLAB SHALL BE SO ASSEMBLED AS TO ENSURE THE STABILITY OF FORM WORKS:-

 - CAMBER FOR NORMAL BEAMS SHALL BE 1 IN 250 OF THE SPAN OR 4MM PER METER OF SPAN AT THE CENTRAL POINT.
 - FOR CANTILEVER BEAMS /SLAB CAMBER AT THE FREE END SHALL BE SPAN / 50 OF THE PROJECTED LENGTH.
 - BEFORE R.C.C. CASTING OF BEAMS/SLAB FORM WORK SHALL BE CHECKED PROPERLY TO AVOID ANY DEFLECTION.
 - 40 MM IN PILES, 20mm IN SLAB, 25mm IN BEAM, 40mm IN COLUMN.
 - ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
 - ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
 - WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO COLUMN UP-TO A LENGTH EQUAL TO 50X BAR DIA DISTANCE MEASURED FROM COLUMN FACE
 - BARS TO BE CUT & BENT NEAR OPENINGS/POCKETS.

NOTES-2

- ALL DIMENSIONS ARE IN IN FEET AND INCHES
- ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.
- ALL TORSIONAL YIELD STRENGTH 500 N/mm.
- ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.
- CLEAR COVER TO MAIN STEEL
40 MM IN PILES, 20mm IN SLAB,
25mm IN BEAM, 40mm IN COLUMN.
- ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
- ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
- WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO COLUMN UP-TO A LENGTH EQUAL TO 50X BAR DIA DISTANCE MEASURED FROM COLUMN FACE
- BARS TO BE CUT & BENT NEAR OPENINGS/POCKETS.


CLIENT :-

ASHWANI SIR

PROJECT :-

FIRST FLOOR SLAB BEAM

SCALE:-	1:100	ISSUED	04.11.25
Plan Number:-	01		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		



JAYPRO INFRATECH PVT. LTD.

Office Address: 1st Floor, Pandooi Place, Boring Road, Patna- 80001

TECHNICAL NOTES & INSTRUCTIONS:-

NOTES AND INSTRUCTIONS INDICATED BELOW SHALL BE FOLLOWED WITH DUE RESPONSIBILITY BY ENGINEER IN-CHARGE DURING EXECUTION OF THE PROJECT. THE ENGINEER IN-CHARGE SHALL STUDY IN DEPTH THE ARCHITECTURAL/STRUCTURAL DRAWINGS OF THE BUILDING /STRUCTURE ENCLOSED, BEFORE EXECUTION AND AMBIGUITY IF ANY NOTICED BY HIM SHALL BE REPORTED TO CONSULTANT, FOR NECESSARY ACTION. ALL DIMENSIONS ARE IN MM FOLLOW WRITTEN DIMENSION ONLY.

ONLY STEEL SHUTTERING / CENTERING SHALL BE USED AT WORK SITE FOR CONSTRUCTION OF R.C.C. FRAMED BUILDING.

QUALITY AND MIX PROPORTION OF MATERIALS TO BE USED IN CONCRETING I.E. WATER / CEMENT / SAND / CHIPS SHALL BE STRICTLY AS PER DESIGN MIX REPORT.

THE CRUSHING STRENGTH OF CUBES PREPARED WITH CONC. MIX AT WORK SITE SHALL CONFORM THE ACCEPTANCE CRITERIA AS MENTIONED IN I.S. 456, 2000.

COVER BLOCK WITH PROPER SIZE & SPECIFIED STRENGTH SHALL BE PROVIDED IN SLAB / BEAM / COLUMN / FOUNDATION BEFORE R.C.C. CASTING @ SPACE NOT EXCEEDING ONE METER C.C. COVER BLOCK SHALL BE PROPERLY TIED WITH THE REINFORCEMENT FOR FIXITY DURING CONCRETE PLACEMENT.

IN CASE OF PILE FOUNDATION IT IS ESSENTIAL TO HAVE ACTUAL PILE LOAD TEST REPORT ALONG WITH PILE CAPACITY BASED ON SOIL PARAMETERS. SO IT IS INSTRUCTED TO GET THE ACTUAL PILE LOAD TEST REPORT BEFORE EXECUTION AND REPORT TO CONSULTANT FOR REVIEW AND FINAL CONCLUSION.

IN CASE OF PILE FOUNDATION HAVING HIGH WATER TABLE USE BENTONITE SOLUTION, CASING AND QUICK SETTING CEMENT, THE ENGINEER IN-CHARGE SHALL TAKE FINAL DECISION AS PER ACTUAL SITE CONDITION.

ALL CONCRETE SHALL BE MACHINE MIXED AND PROPERLY COMPACTED BY VIBRATOR. NOMINAL COVER (I.E. CLEAR CONCRETE COVER TO ALL REINFORCEMENTS, INCLUDING LINKS) FOR FOUNDATION = 50, PILE CAP - 75, COLUMN = 40, BEAM = 30 AND SLAB = 25mm SHALL BE PROVIDED.

PROPER CURING OF R.C.C. SLAB / COLUMN / FOUNDATION / BW PLASTER ETC. SHALL BE PROVIDED.

PROPER ARRANGEMENT FOR SOAKING OF BRICKS SHALL BE ENSURED BY FIELD ENGRS. BEFORE PLACING OF REINFORCEMENT POLYTHENE SHEET SHALL BE SPREAD OVER SHUTTERING TO PREVENT CEMENT SLURRY FROM CONC. MIX.

BEFORE CASTING REINFORCEMENT PLACED SHALL BE DULY MEASURED BY ENGR INCHARGE. THE LENGTH OF REINFORCEMENT SHALL BE DULY MEASURED BY ENGR INCHARGE. LDC = EFFECTIVE DEVELOP LENGTH CONSIDERING COMPRESSION 39X BAR DIA.

1) LAP SPLICE-NOT MORE THAN 50% OF AREA OF STEEL (LONG) IN COLUMN BARS SHALL BE SPliced AT ANY ONE SECTION, LAPPING OR WELDING OF RT. SHALL BE STAGED.

IT SHALL BE WITHIN THE LAPPING ZONE AS SHOWN IN THE DRG. THE LAP LENGTH SHALL NOT BE LESS THAN DEVELOPMENT LENGTH OF ROD AND 30 TIMES DIA OF BAR WHICH IS GREATER.

2) LAP SPLICE IN BEAM SPAN LESS THAN 12M SHALL BE AVOIDED IN NORMAL CASE. IN LONGER SPAN (L> 12M) LAP SHALL BE PROVIDED AS PER APPROVED STR. DRG.

ONLY WRITTEN DIMENSIONS ARE TO BE FOLLOWED.

GRID LINE SHOWS CL OF WALLS.

THE FORM WORK FOR (SPAN >4M) BEAMS & SLAB SHALL BE SO ASSEMBLED AS TO PROVIDE CAMBER AS FOLLOWS :-

CAMBER FOR NORMAL BEAMS SHALL BE 1 IN 250 OF THE SPAN OR 4MM PER METER OF SPAN AT THE CENTRAL POINT

FOR CANTILEVER BEAMS /SLAB CAMBER AT THE FREE END SHALL BE SPAN / 50 OF THE PROJECTED LENGTH

BEFORE R.C.C. CASTING OF BEAMS/SLAB FORM WORK SHALL BE CHECKED PROPERLY TO AVOID ANY DEFECTS.

REMOVAL OF FORM WORK SHALL BE AS PER STRIPPING TIME PRESCRIBED VIDE CL. 11.3 OF I.S. 456-2000 WHICH SHALL BE CHECKED BY E.E./A.E.

IN FRAME STRUCTURE ALL EXTERNALS STAIR WALL SHALL BE 10"THICK AND INTERNAL WALL SHALL BE 5" THICK, EXCEPT MENTIONED.

NECESSARY ARRANGEMENTS SHALL BE MADE FOR PLINTH PROTECTION OF BUILDING AT LEVEL DECIDED BY E.E. TO AVOID WATER LOGGING AROUND BUILDING. THE WIDTH SHALL BE DECIDED AS PER ACTUAL SITE CONDITION BY ENGINEER IN-CHARGE.

WATER PROOFING COMPOUND SHALL BE USED IN CASTING OF SUNKEN SLAB & TERRACE FLOOR SLAB TO PREVENT SEEPAGE.

ALL DESIGN MIX CONCRETE OF GRADE M 25 HAVING MINIMUM CEMENT CONTENT 300 kg/m³, Max. W/C = 0.5 FOR COARSE AGGREGATE 20 mm SIZE. CASTING SHOULD BE DONE AS PER MIX DESIGN.




NOTES:-2

1. ALL DIMENSIONS ARE IN IN FEET AND INCHES
2. ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.
3. ALL TOR STEEL YIELD STRENGTH 500 N/mm .
4. ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.
5. CLEAR COVER TO MAIN STEEL
40 MM IN PILES, 20mm IN SLAB,
25mm IN BEAM, 40mm IN COLUMN.
6. ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
7. ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
8. WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO COLUMN UP-TO A LENGTH EQUAL TO 50X BAR DIA DISTANCE MEASURED FROM COLUMN FACE
9. BARS TO BE CUT & BENT NEAR OPENINGS/POCKETS.

CLIENT :- ASHWANI SIR

PROJECT :-

BEAM REINFORCEMENT INDEX								
BEAM MKD	SIZE		REINFORCEMENT				STIRRUPS	
			TOP REINF.		BOT. REINF.			
	B	D	TOP.M (t1)	TOP.EXT (t2)	BOT.M (b1)	BOT.EXT (b2)	S1	S2
SB1	10"	18"	3-T16	2-T12	3-T16	2-T12	T8@5" c/c	T8@5" c/c



CALE:-	1:100	ISSUED	04.11.20
an Number:-	01		
esign By	Ar. Soni Kumari		
ecked By	Er. Jayprakash Kumar		
proved By	Jaypro Infratech Pvt.Ltd.		

JAYPRO INFRATECH PVT. LTD.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001


SLAB. BEAM SECTION

Follow Now
a Id: [jaypro_infratech](#)
Link Page: [jaypro_infratech](#)

E-mail id: info@javaproinfratech.com, www.javaproinfratech.com, Call Now: 9835852462, 7277008312.

NORTH

WES



SLAB	MAIN (Shorter Span-A)		Distr. (Longer Span-B)		SLAB TYPE
	ROD (dia)	SPACING	ROD (dia)	SPACING	
S-1	T10 mm	6" c/c	T8 mm	6" c/c	CRANK
S-2	T8 mm	6" c/c	T8 mm	6" c/c	CRANK

ALL DIMENSIONS ARE IN IN FEET AND INCHES
ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.
ALL TOR STEEL YIELD STRENGTH 500 N/mm.
ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.
CLEAR COVER TO MAIN STEEL 40 MM IN PILES, 20mm IN SLAB,
25mm IN BEAM, 40mm IN COLUMN.
ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE
ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE
BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
ALL DISTRIBUTION BARS WHEREVER REQUIRED BUT NOT CALLED
OUT SHALL BE 8Tor @250C/C.
THIS DRAWING SHALL BE READ WITH ARCHITECTURAL DRAWINGS.
WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO
COLUMN UPTO A LENGTH EQUAL TO 50X BAR DIA DISTANCE
MEASURED FROM COLUMN FACE

THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
POSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
D, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

NT :- ASHWANI SIR

CT :-

Page No.:	1:100	ISSUED	13.07.25
Number	09		
By	Er. Kumar Neha Ranjan		
and By	Er. Jayprakash kumar		
and By	Jaypro infratech Pvt. Ltd.		


Office Address: 1st Floor, Pandooi Lane, Petaling Jaya, Petaling, 320001

NORTH

WESI

- 10 -

SOUTH



SLAB	MAIN (Shorter Span-A)		Distr. (Longer Span-B)		SLAB TYPE
	ROD (dia)	SPACING	ROD (dia)	SPACING	
S-1	T10 mm	6" c/c	T8 mm	6" c/c	CRANK
S-2	T8 mm	6" c/c	T8 mm	6" c/c	CRANK

OTES:-

ALL DIMENSIONS ARE IN IN FEET AND INCHES

ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.

ALL TOR STEEL YIELD STRENGTH 500 N/mm .

ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.

CLEAR COVER TO MAIN STEEL 40 MM IN PILES, 20mm IN SLAB,
25mm IN BEAM, 40mm IN COLUMN.

ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.

ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE
ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE
BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.

ALL DISTRIBUTION BARS WHEREVER REQUIRED BUT NOT CALLED
OUT SHALL BE 8Tor @250C/C.

THIS DRAWING SHALL BE READ WITH ARCHITECTURAL DRAWINGS.
WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO
COLUMN UPTO A LENGTH EQUAL TO 50X BAR DIA DISTANCE
MEASURED FROM COLUMN FACE

THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
[REDACTED]
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
MAILED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

ENT :-

JECT :-

00


ISSUED 13.07.

10


N

jayprakash kumar

10 of 10



JAYPRO INFRATECH PVT. LTD.
Office Address: 1st Floor, Pandooi
Place, Panjim Road, Panjim, 400001



SLAB	MAIN (Shorter Span-A)		Distr. (Longer Span-B)		SLAB TYPE
	ROD (dia)	SPACING	ROD (dia)	SPACING	
S-1	T10 mm	6" c/c	T8 mm	6" c/c	CRANK
S-2	T8 mm	6" c/c	T8 mm	6" c/c	CRANK

TESTS:-

ALL DIMENSIONS ARE IN FEET AND INCHES
ALL CONCRETE MIX M:20 UNLESS OTHERWISE SPECIFIED.
ALL TOR STEEL YIELD STRENGTH 500 N/mm.
ALL CONCRETE SHALL BE MACHINE MIXED AND MACHINE VIBRATED.
CLEAR COVER TO MAIN STEEL 40 MM IN PILES, 20mm IN SLAB,
5mm IN BEAM, 40mm IN COLUMN.
ALL DIMENSIONS ARE TO BE READ NOT TO BE MEASURED.
ALL DIMENSIONS & DETAILS ARE TO BE VERIFIED WITH THE
ARCHITECTURAL DRAWING AMBIGUITY IF ANY SHOULD BE
BROUGHT TO THE NOTICE OF THE CONSULTING ENGINEERS.
ALL DISTRIBUTION BARS WHEREVER REQUIRED BUT NOT CALLED
OUT SHALL BE 8Tor @250/C.
THIS DRAWING SHALL BE READ WITH ARCHITECTURAL DRAWINGS.
WHEREVER SHOWN BEAM BAR SHALL BE ANCHORED INTO
COLUMN UPTO A LENGTH EQUAL TO 50X BAR DIA DISTANCE
MEASURED FROM COLUMN FACE

THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
PIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETERS, UNLESS OTHERWISE SPECIFIED.

ENT: - **LOWMAN GTE**



JECT:-

LE :	1:100	ISSUED	05.12.25
lumber	09		
gn By	Er. Kumari Neha Ranjan		
ed By	Er. Jayprakash kumar		
ed By	Jaypro infratech Pvt. Ltd.		

Office Address: 1st Floor, Pandooi Lane, Petaling Jaya, Petaling, 320001

Our Services

Architecture Design
Structure Design
Interior Design
Estimating & Costing
Building Construction With Material



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED, COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED. ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- Ground Floor plumbing design

SCALE:- 1:100 ISSUED 29.11.25
Plan Number:- 11

Design By	Ar. Soni Kumari	
Checked By	Er. Jayprakash Kumar	
Approved By	Jaypro Infratech Pvt.Ltd.	

Jaypro Infratech Pvt.Ltd.


Office Address: 1st Floor, Pandooi Place, Boring Road, Patna- 80001

Follow Now :-

You Tube :- [jaypro_infratech](https://www.youtube.com/user/jaypro_infratech)
Facebook Page :- [jaypro_infratech](https://www.facebook.com/jaypro_infratech)
Insta Id :- [jaypro_infratech](https://www.instagram.com/jaypro_infratech/)


E-Mail Id :- info@jayproinfratech.com, www.jayproinfratech.com, Call No:- 9835852462, 7277008312,

NORTH



LEGEND:-

NT- ANTI
AC- ANGLE COCK at 3' h
AC/HF- ANGLE COCK/HEALTH FAUCET GUN at 2' h
CWI- COLD WATER IN at 7' h
HWO- HOT WATER OUT at 7' h
HWM- HOT WATER MIXER at 4' h
CWM- COLD WATER MIXER at 4' h
TAP- TAP at 3' h
HS- HEAD SHOWER at 7' h
BT- BOTTLE TRAP
MP- METROPOLE FLUSH at 3' h
AC-HW- ANGLE COCK FOR HOT WATER at 2' h
AC-CW- ANGLE COCK FOR COLD WATER at 2' h
BT - BOTTLE TRAP
RWP- RAIN WATER PIPE
— 1/2" @ COLD WATER PIPE - SH-40 UPVC
— 3/4" @ HOT WATER PIPE - CPVC SDR - 11 PIPE
— 1" @ COLD WATER PIPE - UPVC PIPE
— 21/2" @ WASTE WATER PIPE - 6KG/CM2 PVC FOR WASH BASIN
— 4" @ WASTE WATER LINE - 6KG/CM2 PVC PIPE
— 6" @ SOIL WATER LINE - 6KG/CM2 PVC PIPE
♀ RISER - 2" @ COLD WATER DOWNTAKE - SH - 40 PVC PIPE
♀ CWP - 2" @ COLD WATER PIPE - SH-40 PVC
♀ WWP - 4" @ WASTE WATER PIPE -PVC 6 KG/CM2
♀ SWP - 6" @ SOIL WATER PIPE -PVC 6 KG/CM2



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- First floor plumbing design


SCALE:-	1:100	ISSUED	29.11.25
Plan Number:-	11		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		

Jaypro Infratech Pvt.Ltd.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001

Our Services

Architecture Design
Structure Design
Interior Design
Estimating & Costing
Building Construction With Material



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED, COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED. ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- Second floor plumbing design

SCALE:-	1:100	ISSUED	29.11.25
Plan Number:-	11		


Design By	Ar. Soni Kumari	
Checked By	Er. Jayprakash Kumar	
Approved By	Jaypro Infratech Pvt.Ltd.	

Jaypro Infratech Pvt.Ltd.


Office Address: 1st Floor, Pandooi Place, Boring Road, Patna- 80001

Our Services

Architecture Design
Structure Design
Interior Design
Estimating & Costing
Building Construction With Material



LEGEND		
SYMBOL	DESCRIPTION	HEIGHT
△	CEILING FAN	ON CEILING
◇	CHANDELIER LIGHT POINT	ON CEILING
—	40WX40" TUBE LIGHT FITTING	8'6"
○	BLUB	8'6"
●	NIGHT BLUB	8'6"
—	C.F.L	ON CEILING
○○	SPORT LIGHT	ON CEILING
○○	CEILING LIGHT	ON CEILING
○○	FLASH JUNCTION BOX	ON CEILING
SB	SWITCH BOARD	4'6" HT
—	BED SWITCH	2'6" HT
—	TWO WAY SWITCH	ON SWITCH
—	5 AMPS SWITCH SOEKET	1'6" HT
—	15 AMPS SWITCH SOEKET	1'6" HT
—	25 AMPS SWITCH SOEKET (A.C)	1'6" HT
—	CALL BELL BUZZER	1'6" HT
—	CALL BELL PUSH	4'6" HT
—	OUT LET FOR TELEPHONE	1'6" HT
—	OUT LET FOR TV	1'6" HT
—	EXHAUST FAN (IN TOI & KIT)	
—	TABLE LAMP	
—	ROOT OF TV TELEPHONE WIRING	
—	ROOT OF POINT WIRING (25MM)	
—	ROOT OF POINT WIRING (19MM)	
—	ROOT OF CIRCUIT WIRING (19MM)	
—	ROOT OF SUB MAIN WIRING (25MM)	
—	WALL FAN	
—	DISTRIBUTION BOARD	
—	METERING PANAL	




THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- Ground Floor Electric design

SCALE:- 1:100 ISSUED 29.11.25
Plan Number:- 11

Design By Ar. Soni Kumari
Checked By Er. Jayprakash Kumar
Approved By Jaypro Infratech Pvt.Ltd.



Jaypro Infratech Pvt.Ltd.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001

Follow Now :-

You Tube :- jaypro_infratech
Facebook Page :- jaypro_infratech
Insta Id :- jaypro_infratech


E-Mail Id :- info@jayproinfratech.com, www.jayproinfratech.com, Call No:- 9835852462, 7277008312,

Our Services

Architecture Design
Structure Design
Interior Design
Estimating & Costing
Building Construction With Material

LEGEND

SYMBOL	DESCRIPTION	HEIGHT
—	CEILING FAN	ON CEILING
—	CHANDELIER LIGHT POINT	ON CEILING
—	40WX40" TUBE LIGHT FITTING	8'6"
—	BLUB	8'6"
—	NIGHT BLUB	8'6"
—	C.F.L	ON CEILING
—	SPORT LIGHT	ON CEILING
—	CEILING LIGHT	ON CEILING
—	FLASH JUNCTION BOX	ON CEILING
—	SWITCH BOARD	4'6" HT
—	BED SWITCH	2'6" HT
—	TWO WAY SWITCH	ON SWITCH
—	5 AMPS SWITCH SOEKET	1'6" HT
—	15 AMPS SWITCH SOEKET	1'6" HT
—	25 AMPS SWITCH SOEKET (A.C)	1'6" HT
—	CALL BELL BUZZER	1'6" HT
—	CALL BELL PUSH	4'6" HT
—	OUT LET FOR TELEPHONE	1'6" HT
—	OUT LET FOR TV	1'6" HT
—	EXHAUST FAN (IN TOI & KIT)	
—	TABLE LAMP	
—	ROOT OF TV TELEPHONE WIRING	
—	ROOT OF POINT WIRING (25MM)	
—	ROOT OF POINT WIRING (19MM)	
—	ROOT OF CIRCUIT WIRING (19MM)	
—	ROOT OF SUB MAIN WIRING (25MM)	
—	WALL FAN	
—	DISTRIBUTION BOARD	
—	METERING PANAL	



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- First Floor Electric design

SCALE:- 1:100 ISSUED 29.11.25
Plan Number:- 11

Design By	Ar. Soni Kumari	
Checked By	Er. Jayprakash Kumar	
Approved By	Jaypro Infratech Pvt.Ltd.	


Jaypro Infratech Pvt.Ltd.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001

Follow Now :-

You Tube :- jaypro_infratech
Facebook Page :- jaypro_infratech
Insta Id :- jaypro_infratech


E-Mail Id :- info@jayproinfratech.com, www.jayproinfratech.com, Call No:- 9835852462, 7277008312,



NORTH


WEST

EAS



SOUTH

LEGEND		
SYMBOL	DESCRIPTION	HEIGHT
	CEILING FAN	ON CEILING
	CHANDELIER LIGHT POINT	ON CEILING
	40WX40" TUBE LIGHT FITTING	8'6"
	BLUB	8'6"
	NIGHT BLUB	8'6"
	C.F.L.	ON CEILING
	SPORT LIGHT	ON CEILING
	CEILING LIGHT	ON CEILING
	FLASH JUNCTION BOX	ON CEILING
	SWITCH BOARD	4'6" HT
	BED SWITCH	2'6" HT
	TWO WAY SWITCH	ON SWITCH
	5 AMPS SWITCH SOEKET	1'6" HT
	15 AMPS SWITCH SOEKET	1'6" HT
	25 AMPS SWITCH SOEKET (A.C.)	1'6" HT
	CALL BELL BUZZER	1'6" HT
	CALL BELL PUSH	4'6" HT
	OUT LET FOR TELEPHONE	1'6" HT
	OUT LET FOR TV	1'6" HT
	EXHAUST FAN (IN TOI & KIT)	
	TABLE LAMP	
	ROOT OF TV/TELEPHONE WIRING	
	ROOT OF POINT WIRING (25MM)	
	ROOT OF POINT WIRING (19MM)	
	ROOT OF CIRCUIT WIRING (19MM)	
	ROOT OF SUB MAIN WIRING (25MM)	
	WALL FAN	
	DISTRIBUTION BOARD	
	METERING PANAL	



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR



PROJECT :- Second Floor Electric design

SCALE:-	1:100	ISSUED	29.11.25
Plan Number:-	11		
Design By	Ar. Soni Kumari		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		

Jaypro Infratech Pvt.Ltd.

Office Address: 1st Floor, Pandooi Place, Boring Road, Patna- 80001

Our Services
 Architecture Design
 Structure Design
 Interior Design
 Estimating & Costing
 Building Construction With Material



THIS DRAWING HAS NOT BEEN PUBLISHED AND IS THE SOLE PROPERTY OF
 PURPOSE AS STATED IN THE AGREEMENT AND IT SHALL NOT BE REPRODUCED,
 COPIED, LENT OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY, NOR USED
 FOR ANY OTHER PURPOSE OTHER THAN FOR WHICH IT IS FURNISHED.
 ALL DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED.

CLIENT :- ASHWANI SIR

PROJECT :- REINFORCEMENT
DETAILS OF STAIR

SCALE:-	1:100	ISSUED	29.11.25
Plan Number:-	01		
Design By	Er.Rishav Kumar		
Checked By	Er. Jayprakash Kumar		
Approved By	Jaypro Infratech Pvt.Ltd.		

JAYPRO INFRATECH PVT. LTD.

Office Address: 1st Floor, Pandooi
Place, Boring Road, Patna- 80001